

HUNTER SWING JOINTS



- Swivel elbows on both ends
- Pressure rated to 10 bar
- Each end can rotate in multiple directions
- Great for 1/2" & 3/4" pop-up sprinklers
- 6" & 12" options available

Catalogue No	Description	Price £	Box Qty
2SJH1106	1/2"M Elbow each end x 6" long	2.38	150
2SJH1206	1/2"M Elbow x 3/4"M Elbow x 6" long	2.71	200
2SJH2206	3/4"M Elbow each end x 6" long	2.61	150
2SJH1112	1/2"M Elbow each end x 12" long	2.85	100
2SJH1212	1/2"M Elbow x 3/4"M Elbow x 12" long	2.99	100
2SJH2212	3/4"M Elbow each end x 12" long	2.99	100



Catalogue No	Description	Price £	Box Qty
2SJH165412	1" BSP inlet x 1" BSP outlet Triple Top	48.45	15
2SJH168412	1" BSP inlet x 1.5" ACME outlet Triple Top	48.45	15
2SJH260412	1.25" BSP inlet x 1.25" ACME outlet Triple Top	63.65	15
2SJH268412	1.25" BSP inlet x 1.5" ACME outlet Triple Top	63.65	15
2SJH360212	1.5" BSP inlet x 1.5" ACME outlet standard	53.20	15
2SJH360412	1.5" BSP inlet x 1.5" ACME outlet Triple Top	76.00	10
2SJH16U212	1" Triple Swing Joint (Non-Turn) QCV stabiliser	64.60	15

HUNTER FLEXIBLE TUBE & SPIRAL ELBOWS

- Equivalent to Funny Pipe
- 1/2" flexible tube for connecting sprinklers
- 1/2" & 3/4" spiral barbed elbows
- Tubing comes in 30m (100') rolls

Catalogue No	Description	Price £	Box Qty
2SJBFLX-30	Flexible 1/2" tubing 30m roll	39.90	50
2SJBEM	Spiral barbed elbow 1/2"BSPM	0.31	200
2SJBEM	Spiral barbed elbow 3/4"BSPM	0.33	200
2SJBETOOL	Installation Tool	19.60	150



HUNTER BRASS QUICK COUPLERS (QC)



Catalogue No	Description	Price £
HSZHQ3RC	QC Valve 3/4" inlet.	65.55
HSZHQ5LR	QC Valve 1" inlet.	138.70
	Locking rubber cover	
HSZHK33	QC Key 3/4" outlet.	45.60
HSZHK55	QC key 1" outlet	114.00
HSZHLK	Lid Key	12.35
HSZHS0	3/4" BSP Hose Swivel elbow	71.25
HSZHS2B	1" BSP Hose Swivel elbow	81.70

DURA SWING JOINTS

- Swing joints for valve-in-head sprinklers & other applications where static pressure will be applied to the joints
- Rigid PVC with o-ring joints in the elbows

Catalogue No	Inlet BSP "M	Outlet BSP "M	Length Inch	Price £	Box Qty
2SJD2208	3/4	3/4	8	20.05	25
2SJD2212	3/4	3/4	12	21.44	25
2SJD3308	1	1	8	28.46	10
2SJD3312	1	1	12	31.90	10
2SJD3318	1	1	18	35.36	10
2SJD4408	1 1/4	1 1/4	8	35.08	10
2SJD4412	1 1/4	1 1/4	12	40.22	10
2SJD5512	1 1/2	1 1/2	12	51.47	10

Catalogue No	Inlet BSP "M	Outlet Acme	Length Inch	Price £	Box Qty
2SJDA4312	1	1 1/4	12	31.90	10
2SJDA4412	1 1/4	1 1/4	12	38.21	10
2SJDA5312	1	1 1/2	12	28.79	10
2SJDA5412	1 1/4	1 1/2	12	38.21	10
2SJDA5512	1 1/2	1 1/2	12	51.47	10

DURA ADDITIONAL ELBOWS

Catalogue No	Inlet Female Swing	Outlet Male Swing	Price £	Box Qty
2SJDE22	3/4	3/4	4.98	50
2SJDE33	1	1	5.25	50
2SJDE44	1 1/4	1 1/4	6.94	50
2SJDE55	1 1/2	1 1/2	9.72	50

Catalogue No	Inlet Female Swing	Outlet BSP "M	Price £	Box Qty
2SJDSEFS33	1	1	5.25	50

Catalogue No	Inlet Female Swing	Outlet Acme	Price £	Box Qty
2SJDEA33	1	1	9.57	50
2SJDEA43	1	1 1/4	11.82	50
2SJDEA53	1	1 1/2	11.82	50
2SJDEA44	1 1/4	1 1/4	14.07	50
2SJDEA54	1 1/4	1 1/2	14.07	50
2SJDEA45	1 1/2	1 1/4	14.07	50
2SJDEA55	1 1/2	1 1/2	17.78	50

MARLEX STREET ELBOWS



Catalogue No	Description	Price £	Box Qty
2M4M4F	1 1/4"MF BSP	2.98	25
2M5M5F	1 1/2"MF BSP	9.37	25





- All MP Rotators require a Hunter Pro-Spray or shrub-head body to fit into
- The PRS-40 pressure regulated Pro-Spray body is regulated to 2.8 bar (40psi) which is ideal
- Four models: MP1000, 2000, 3000, 3500
- The 90° option adjusts from 90°-210°
- The 210° option adjusts from 210°-270°
- The 360° option is a true full circle head
- Matched precipitation; the precipitation rate is proportionate with the spray coverage
- Radius can be reduced by 25% on all models
- Use the MP Tool to make adjustments
- Colour-coded for easy identification
- 2 year warranty

MP 1000 (UP TO 4.5M RADIUS)

Catalogue No	Description	Colour	Price £
HSMP10-090	90-210°	Maroon	9.50
HSMP10-210	210-270°	Light Blue	9.50
HSMP10-360	Full Circle	Olive	9.50

MP 2000 (UP TO 6.7M RADIUS)

Catalogue No	Description	Colour	Price £
HSMP20-090	90-210°	Black	9.50
HSMP20-210	210-270°	Green	9.50
HSMP20-360	Full Circle	Red	9.50

MP 3000 (UP TO 9.1M RADIUS)

Catalogue No	Description	Colour	Price £
HSMP30-090	90-210°	Blue	9.50
HSMP30-210	210-270°	Yellow	9.50
HSMP30-360	Full Circle	Grey	9.50

MP 3500 (UP TO 11M RADIUS)

Catalogue No	Description	Colour	Price £
HSMP35-090	90-210°	Light Brown	9.50

MP STRIPS (UP TO 4.5M RADIUS)

Catalogue No	Description	Colour	Price £
HSMP LCS	Left corner 1.5x4.6	Ivory	9.50
HSMP RCS	Right corner 1.5x4.6	Copper	9.50
HSMP SS	Side strip 1.5x9.1	Brown	9.50
HSMP CS	Corner 4.1M	Turquoise	9.50

MP 800SR - SHORT RANGE (UPTO 3.5M)

Catalogue No	Description	Colour	Price £
HSMP80SR-90	90-210°	Orange/Grey	9.50
HSMP80SR-360	Full Circle	Lime/Grey	9.50

MP TOOL



Catalogue No	Description	Price £
HSZMPTOOL	MP Rotator adjustment tool	1.47
HSZ172000	Hunter wrench / key	1.19
HSMPCSCREEN	Fine Filter for MP Rotator	0.69
HSMPGAUGE	MP Gauge	47.50

HUNTER PRO ADJUSTABLE SPRAY NOZZLES



- Designed to fit Pro-Spray & PRS-30 bodies
- Matched precipitation for different angles
- Adjust with your fingers or the Hunter key
- Large droplets to withstand light winds
- Color coded for easy identification
- Adjustable 0 - 360 degrees
- Recommended operating pressure 2 bar
- Hence the PRS-30 body is designed for sprays

Catalogue No	Description	Price £
HSPSN04A	4' (1.2m)	1.47
HSPSN06A	6' (1.8m)	1.47
HSPSN08A	8' (2.4m)	1.47
HSPSN10A	10' (3m)	1.47
HSPSN12A	12' (3.7m)	1.47
HSPSN15A	15' (4.6m)	1.47
HSPSN17A	17' (5.2m)	1.47
HSPSN08A-SN	25-360 deg. 2.6m, stream nozz	1.47
HSPSN16A-SN	25-360 deg. 5.3m, stream nozz	1.47
HSSRN04H	4H 180 deg Short Range Nozzle	1.47
HSSRN04Q	4Q 90 deg Short Range Nozzle	1.47
HSSRN06H	6H 180 deg Short Range Nozzle	1.47
HSSRN06Q	6Q 90 deg Short Range Nozzle	1.47

HUNTER STRIP PATTERN SPRAY NOZZLES



- Nozzles will fit in the Pro-spray body or the PRS-30 pressure regulated body
- For narrow strips: rectangular pattern
- To operate these at optimal pressure, use the PRS-30 pressure regulated body

Catalogue No	Description	Price £
HSPSNLCS	Left corner 5' x 15' (1.5m x 4.5m)	1.71
HSPSNRCS	Right corner 5' x 15' (1.5m x 4.5m)	1.71
HSPSNCS	Center strip 5' x 30' (4.5m each way)	1.71
HSPSNES	End strip 5' x 30' (1.5m x 4.5m)	1.71
HSPSNSSS30	Side strip 5' x 30' (1.5m x 9m)	1.71

PCN BUBBLER NOZZLES



- Fits into the Pro-spray pop or shrubhead.
- Up to 7.6 litres/minute flow rate.
- Irrigation system pressure range 1-4 bar.

Catalogue No	Description	Price £
HSMSBN-050Q	1.9 l/min, 1/4 circle	2.71
HSPCN-02	0.9 l/min, trickle pattern	2.71
HSPCN-05	1.9 l/min, trickle pattern	2.71
HSPCN-10	3.8 l/min, umbrella pattern	2.71
HSPCN-20	7.6 l/min, umbrella pattern	2.71

PCB BUBBLER NOZZLES (1/2" BSP)



- Similar to the PCN Bubbler, but 1/2" BSPF
- Up to 7.6 litres/minute flow rate
- Irrigation system pressure range 1-4 bar

Catalogue No	Description	Price £
HSPCB-02	0.9 l/min, trickle pattern	5.42
HSPCB-05	1.9 l/min, trickle pattern,	5.42
HSPCB-10	3.8 l/min, umbrella pattern,	5.42
HSPCB-20	7.6 l/min, umbrella pattern,	5.42

AFB ADJUSTABLE FLOOD BUBBLER 1/2" BSP



- Similar to the PCB Bubbler, but adjustable flow
- Up to 7.6 litres/minute flow rate
- Irrigation system pressure range 1- 4 bar

Catalogue No	Description	Price £
HSPAFB	Up to 7.6 l/min, umbrella pattern	3.90

STANDARD PRO-SPRAY BODY


- 1/2" BSP female inlet on all models
- Compatible with female threaded nozzles
- Recommended pressure range 1 - 7 bar
- Check-valve models; check to 3m elevation
- Side & bottom inlets on the 6" & 12" models
- Pressure-activated wiper seal

Catalogue No	Description	Price £	Box Qty
HSPROS-00	Shrub-adaptor	1.09	250
HSPROS-02	2" pop-up height	2.61	50
HSPROS-04	4" pop-up height	2.61	50
HSPROS-06	6" pop-up height	11.04	25
HSPROS-12	12" pop-up height	16.10	25
HSPROS-04-CV	4" pop-up c/w check valve	5.32	50
HSPROS-06-CV	6" pop-up c/w check valve	13.78	25
HSZ437400	Check valve for Pro-Spray	1.49	25

PRS-30 PRESSURE-REGULATED BODY ONLY


- Pro-Spray body with built-in 30psi (2.1 bar) pressure regulator to control the flow rate
- Designed for Hunter adjustable spray nozzles
- Check valve models; check to 3m elevation
- Side & bottom inlets on the 6" & 12" models
- Pressure-activated wiper seal
- Tan coloured top denotes PRS-30

Catalogue No	Description	Price £	Box Qty
HSPRS30-00	2.1 bar regulated shrub-head	6.10	25
HSPRS30-04	2.1 bar regulated 4" pop-up	7.72	50
HSPRS30-12	2.1 bar regulated 12" pop-up	19.95	25
HSPRS30-04-CV	2.1 bar reg. 4" pop c/w check valve	10.17	50
HSPRS30-06-CV	2.1 bar reg. 6" pop c/w check valve	21.38	25
HSPRS30-12-CV	2.1 bar reg. 12" pop c/w check valve	26.13	25

PRS-40 PRESSURE-REGULATED BODY ONLY


- Pro-Spray body with built-in 40 psi (2.8 bar) pressure regulator to control the flow rate
- Designed for the MP Rotator
- Check-valve models; check to 3m elevation
- 5 year warranty
- Heavy duty spring
- Side & bottom inlets on the 6" & 12" models
- Pressure-activated wiper seal
- Grey coloured top denotes PRS-40

Catalogue No	Description	Price £	Box Qty
HSPRS40-00	2.8 bar regulated shrub-head	6.10	25
HSPRS40-04-CV	2.8 bar reg. 4" pop c/w check valve	10.17	50
HSPRS40-06-CV	2.8 bar reg. 6" pop c/w check valve	21.38	25
HSPRS40-12-CV	2.8 bar reg. 12" pop c/w check valve	26.13	25

PGJ ROTOR


- 2 year warranty on all "P" series rotors
- 1/2" BSP female inlet
- Complete with 8-nozzle rack
- Radius 4.3 - 11.6 metres
- Recommended pressure range 1.4-6.9 bar
- 14 degree nozzle trajectory
- Pop-up versions in 4", 6" & 12" height

Catalogue No	Description	Price £	Box Qty
HSPGJ-00	Shrub version	13.70	25
HSPGJ-04	4" Pop-up	12.72	25
HSPGJ-06	6" Pop-up	27.08	25
HSPGJ-12	12" Pop-up	38.00	12
HSZ302500	Check valve for PGJ	1.49	25

PGP ULTRA ROTOR


- 3/4" female BSP inlet
- Nozzle rack has 8 standard blue nozzles and 4 grey low angle nozzles
- Radius 4.9-14 metres
- Flow rate 0.07-3.23 m3/hour
- Recommended pressure 1.4 to 7 bar
- 25 degree standard blue nozzle trajectory
- 13 degree low angle grey trajectory
- Check valve will hold max. 3m elevation

Catalogue No	Description	Price £	Box Qty
HSPGP-00	Shrub-head	15.20	20
HSPGP-00-CV	Shrub-head c/w check valve	20.90	160
HSPGP-04	4" Pop-up height	15.20	20
HSPGP-04-CV	4" pop-up c/w check valve	23.04	20
HSZ142300	Check valve & screen assy for PGP	1.49	25

I-20 COMMERCIAL ROTOR


- Radius up to 14 metres
- 3/4" BSP female inlet
- Complete with 8 standard & 4 low angle nozzles
- Part & full circle in one sprinkler
- Flo-Stop control; reduce the radius and even turn the sprinkler off through the top
- Drain check valve (3m) standard on all models
- Flow rate 0.07-3.23 m3/hour
- Recommended pressure 1.4 to 7 bar
- 25 degree standard blue nozzle trajectory
- 13 degree low angle grey trajectory

Catalogue No	Description	Price £	Box Qty
HSI20-04	4" Pop-up, plastic riser	24.46	20
HSI20-04-SS	4" Pop-up, stainless riser	34.25	20
HSI20-06-SS	6" Pop-up, stainless riser	46.97	20
HSI20-12	12" Pop-up, plastic riser	50.88	20

I-25 COMMERCIAL ROTOR



- Radius 11.9 - 21.6 metres
- 1" BSP female inlet
- Part & full circle in one sprinkler
- Drain check valve (3m) standard on all models
- Flow rate 0.82 - 7.24 m³/hour
- Recommended pressure 4-7 bar
- 25 degree nozzle trajectory

Catalogue No	Description	Price £	Box Qty
HSI25-04	4" Pop-up, plastic riser	53.82	12
HSI25-04-SS	4" Pop-up, stainless riser	70.45	12
HSI25-04-SSH	1-25 4" s/steel Pop-up high speed	171.24	12
HSI25-06	6" Pop-up, plastic riser	71.43	12
HSI25-06-SS	6" Pop-up, stainless riser	86.11	12

I-40 COMMERCIAL ROTOR



- All I-40 models have stainless risers
- 1" BSP female inlet
- Opposing nozzle version provides greater throw
- Standard model Radius 13 - 21.3 metres
- Opposing nozzle radius 15 - 23.2 metres
- Recommended pressure range 2.8 - 7 bar
- Part & full circle in one model
- 5 Year warranty

Catalogue No	Description	Price £	Box Qty
HSI40-04-SS	4" Pop-up	106.66	12
HSI40-04SSO	4" pop-up, opposing nozzles	121.33	12
HSI40-06-SS	6" Pop-up	122.31	12
HSI40-06SSO	6" pop-up, opposing nozzles	132.10	12
HSI40-TC	Turf Cup for I40	40.51	25

I 80 TURF ROTOR



- All I-80 models have Ratcheting stainless steel riser
- 1½" BSP plus Reducing Bush to 1"
- Exclusive ProTech Turf Cup System
- No-dig servicing of riser assembly - No-dig arc adjustments
- Quick-release turf cup assembly
- Threads in cup lock/retain the turf
- Exclusive Total-Top-Service (TTS) design
- I-80 Standard Radius: 11.3 m to 28.7 m
- I-80-ON Radius: 14.9 to 29.6 m
- Warranty period: 5 years

Catalogue No	Description	Price £	Box Qty
HSI80-00-SS38	Riser Mounted Adjustable	184.00	6
HSI80-04-SS38	4" Pop Up Adjustable	184.00	6
HSI80-04-SSO38	4" Pop Up Opposing Nozzles	199.00	6
HSI80-TC	Turf Cup Kit	177.00	NA

HUNTER I-90 LARGE TURF ROTOR



- 1.5" BSP female bottom inlet
- Radius up to 30.8 metres
- Flow rate 5 - 18.6 m³/hour
- Recommended pressure range 4 - 7.5 bar
- Pop-up height 3"
- Plastic riser only (no stainless options)
- 5 year warranty

Catalogue No	Description	Price £	Box Qty
HSI90-ADV	Adjustable arc	198.55	6
HSI90-36V	Full Circle	198.55	6
HSI90-TC	Turf cup kit for I-90	66.50	NA

ST-90 / STG-900 SYSTEM



ST-90



STG-900

- Designed for synthetic sports pitches
- Radius 31 - 36.6 metres
- Flow rate 16.9 - 20.9 m³/hour
- Required pressure range 6.9 - 8.3 bar
- 5 year warranty

Catalogue No	Description	Price £
HSSTG-090	ST-90 Series pop-up	375.25
HSSTG-900	STG-900 series pop-up	403.75

HUNTER ST-1600 SYSTEMS



ST-1600B



ST-1600BR

- Designed for synthetic sports pitches
- Radius 32.5 - 50.3 metres
- Flow rate 22 - 74 m³/hour
- Required pressure range 4 - 8 bar



Vault for ST-1600-B system

Catalogue No	Description	Price £
HSST-1600-BHS	ST-1600B series pop-up High Speed	1448.75
HSST-1600-BR	ST-1600BR series riser mounted	769.50
Accessories:		
HSST-1600-IBS	In Fill Barrier Sytem	185.25
HST243642-B	Vault for ST-1600-B system	1610.25
HSST-BKT1600	ST-1600 Hanger Bracket	308.75

HUNTER HCV CHECK VALVES



- Adjusts to compensate for elevation changes up to 11m
- Meets schedule 80 specification
- Different models for ½" & ¾" sprinklers

Catalogue No	Description	Price £
HSV50F05F	½" female inlet x ½" female out	7.10
HSV50F05M	½" female inlet x ½" male out	7.10
HSV07F07M	¾" female inlet x ¾" male out	8.08

G835 GOLF HEADS



- Radius 5.5m - 15.2m
- Designed for golf Tee irrigation
- G835E is Adjustable arc (50°-360°)
- 8 multi-trajectory nozzles (15-25°)
- Flow rate 7-48 litres per minute
- Required pressure range 2.8- 4.5 bar
- 2 regulated pressure options available: 3.5 bar (50psi) & 4.5 bar(65psi)
- TTS Compartment is large enough to fit a Hunter decoder & cable connections
- VIH Sprinkler complete with Hunter 24vac coil
- 3 year warranty

Catalogue No	Description	Price £
HSG835E	Adjust. arc, electric VIH, 1 1/2" acme	380.00
HSG35B	Adjustable arc, block, 1 1/4" acme	99.75
SPARE PARTS:		
HSZ563400	Inlet valve assy for 800 series	67.00

G870 GOLF HEADS



- Max. radius 22.9m(full circle) 21.6m (part circle)
- G870E is Full Circle
- G875E is Adjustable arc (50°-360°)
- 6 full circle nozzles (25°)
- 9 part circle nozzles (25°)
- Flow rate 1.75 - 7.6 m3/hour (30-127 l/min)
- Required pressure range 2.8- 6.9 bar
- 3 regulated pressure options available: 3.5 bar (50psi) 4.5 bar(65psi) & 5.6 bar(80psi)
- 3 year warranty

Catalogue No	Description	Price £
HSG70B	Full circle, block, 1 1/4" acme	140.00
HSG75B	Adjustable arc, block, 1 1/4" acme	160.00
SPARE PARTS:		
HSZ563400	Inlet valve assy for 800 series	67.00
HSZ474571	Replacement Riser assembly G875	99.00
HSZ474211	Replacement Riser assembly G75B	107.00
HSZ450400	Upper Riser Seal G875	1.60
HSZ348900	Riser Seal G75B	2.15

*While stocks last

ACME-TO-BSP ADAPTOR BUSHES

- Use the 1.25" acme adaptors for the G35B, G75B & G85B sprinklers
- Use the 1.5" acme adaptors for all Hunter electric VIH sprinklers

Catalogue No	Description	Price £
HSGB3AM3F	1" acme male x 1" BSP female	8.97
HSGB4AM3F	1 1/4" acme male x 1" BSP female	8.97
HSGB4AM5F	1 1/4" acme male x 1 1/2" BSP female	8.97
HSGB5AM3F	1 1/2" acme male x 1" BSP female	13.68
HSGB5AM4F	1 1/2" acme male x 1 1/4" BSP female	13.68
HSGB5AM5F	1 1/2" acme male x 1 1/2" BSP female	13.68

G880 SERIES GOLF HEADS



- Radius 20.4m- 26.8m
- Comes with std nozzle no 25
- G880E is Full Circle
- G885E is Adjustable arc (50°-360°)
- Wide range of nozzles including 12 standard trajectory (22.5°) & 9 low angle (15°) nozzles
- Also a range of 8 contour back nozzles
- Flow rate 5 - 13 m3/hour (83-217 l/min)
- Required pressure range 3.5- 7 bar
- 3 regulated pressure options available: 3.5 bar (50psi) 4.5 bar(65psi) & 5.6 bar(80psi)
- 3 year warranty
- The G85B is a block sprinkler (no solenoid)
- It can be reconfigured as a part-circle head or a true full circle head
- In part circle the G885/G85B can include "rooster tail" opposing nozzles to irrigate the surrounds of a golf green

Catalogue No	Description	Price £
HSG880E	Full circle, electric VIH, 1 1/2" acme	267.18
HSG885E	Adjust. arc, electric VIH, 1 1/2" acme	380.00
HSG885DIH	G885 Golf Head DIH PC 1 1/2" acme	546.25
HSG80B	Full Circle Block 1 1/4" acme	161.50
HSG85B	Adjustable arc, block, 1 1/4" acme	185.25
SPARE PARTS:		
HSZ563400	Inlet valve assy for 800 series	67.00
HSZ460023	G885/85Nozzle pack 10-20	28.00
HSZ460024	G885/85Nozzle pack 23-33	18.00
HSZ460025	G885/85Nozzle pack 38-53	23.00
HSZ272112	G885/858 Primary Nozzle No 20	5.00
HSZ272103	G885/85 Primary Nozzle 33	5.00
HSZ272106	G885/858 Primary Nozzle No 48	5.00

G900 SERIES GOLF HEADS



- Radius 22.3m- 31.7m (111-317 l/min)
- 1.5" acme inlet
- G990E is Full Circle
- G995E is Adjustable arc (40°-360°)
- 8 standard trajectory nozzles (22.5°)
- 8 low angle trajectory nozzles (15°)
- Flow rate 7 - 19 m3/hour
- Required pressure range 5.5- 8.3 bar
- 3 regulated pressure options available: 5.6 bar(80psi), 7 bar (100psi), 8.4 bar (120psi)
- TTS Compartment is large enough to fit a Hunter decoder & cable connections
- 3 year warranty

Catalogue No	Description	Price £
HSG990E	Full circle, electric VIH, 1 1/2" acme	390.00
HSG995E	Adjust. arc, electric VIH, 1 1/2" acme	425.00
SPARE PARTS:		
HSZ643200	Inlet valve assy for 900 series	42.80
HSZ463004	Replacement Riser assembly G995	166.00
HSZ464363	G90 Primary Nozzle 33 (x25)	36.40
HSZ191800	G990/995 Nozzle - Short range	2.00
HSZ378105	G995 Top Cap	8.05



Hunter® Rootzone



RZWS - ROOT ZONE WATERING SYSTEM

- For shrubs, bushes, small and large trees
- Pre-assembled water system
- Incorporating Bubbler, swing joint and removable cap.
- Allows air flow to the roots.

Catalogue No	Description	Price £
HSRZW10	25cm (10") RZWS and cap. Bubbler, swing joint and check valve not included	16.15
HSRZW10-25	25cm (10") with factory fitted 0.9 lpm Bubbler	19.95
HSRZW18-25	45cm (18") with factory fitted 0.9 lpm Bubbler	39.90
HSRZW36-25	90cm (36") with factory fitted 0.9 lpm Bubbler	47.50

Hunter® Tools



Catalogue No	Item	Description	Price £
HSZ123200	1	Nozzle Insertion Collar	1.00
HSZ382800	2	Arc adjustment tool (G85B, G885E)	2.50
HSZ280100	3	Hunter Pitot gauge	65.00
HSZ460302	4	Guzzler Hand Pump	45.00
HSZ053191	5	T-Handle Tool	1.00
HSZ052510	6	Snap-ring Removal Tool	23.00
HSZ604000	7	Valve Insert/ Removal Tool G800	133.00
HSZ052805	8	Valve Insertion/Removal Tool (G900)	145.00
HSZ475600	9	Valve&Snapping Removal Pliers~G800	45.00
HSZG90HS100	10	Hose Swivel Adaptor for G90/G900	99.75
HSZG800HS100	11	Hose Swivel Adaptor for G800 Series	99.75
HSZ475700	12	Hunter Golf Rotor Tool Kit	495.00
HST517600	13	ST-1600 Tool , Gear Drive R & R	58.00
HSZ160700	14	3/4" Spotshot	50.00
HSZ160705	14	1" Spotshot	50.00
HSZ984400	15	1-80 Service Tool	30.00
HSZ172000	16	Hunter wrench / key	1.19

Hunter® Spare Parts

CONTROLLER SPARES

Catalogue No	Description	Price £
HCZETADAPTOR	ET Adaptor	60.00
HSZ122516	Hunter Key to fit all controllers	5.00
HCZ124705	I Core Controller Front Panel	175.00
HCZ387300	ICC Controller Lock and Key Set	12.00
HSZ154628	I-CORE INTERNAL TRANSFORMER	40.00
HCZ52-6200	PCC PRO-C Front Panel	80.00

GOLF ROTOR SPARES

Catalogue No	Description	Price £
HSZ052383	G70B/75B/875 Riser Seal	1.05
HSZ349100	G70B/G75B Riser Seal Uppersupport	1.05
HSZ403400	G70B/G75B Upper snap ring (black)	11.50
HSZ461532	G75/G875 Std Nozzle set (adj arc)	16.00
HSZ382400	G75B Snap Ring Assy (Upper) Black	3.20
HSZ562800	G800E Snap Ring-lower (white)	3.20
HSZ271900	G85B Screen/Check Valve for	6.50
HSZ450500	G875 Riser Seal	2.15
HSZ610100	G875 Snap Ring Assembly	9.10
HSZ256500	G885 Face Sea	8.00
HSZ255300	G885 Rubber Logo Cap Assembly	9.50
HSZ450100	G885 Upper Snap Ring Assy (Black)	9.10
HSZ674800	G885E Pressure Regulator for	26.75
HSZ460020	G885E Replacement Riser Assem	180.00
HSZ271000	G885E Variable Stator Assy	12.00
HSZ454200	G885 Selector Cap Yellow	1.85
HSZ461536	G885E/G995E Grey Selector Cap	7.60
HSZ525700	DIH Brace Decoder Support - Yellow	5.00
HSZ353600	DIH-100 1 Station Decoder/Solenoid	198.00
HSZ686500	DIH-200 2 Station Decoder/Solenoid	298.00
HSZ464364	G90 Primary Nozzle No 38 Red (25)	25.00
HSZ052830	G900 series Lower snap ring (white)	3.20
HSZ430700	G900 series snap ring assy (black)	4.30
HSZ195701	G995 NOZZLE - MID RANGE	2.00
HSZ461204	G995E primary nozzle pack 8	15.00
HSZ473900	G995E Rubber Cover	115.00

I SERIES SPARES

Catalogue No	Description	Price £
HSZ463403	I31 / I25 / G75 Nozzle - Orange	25.00
HSZ463408	I31 / I25 / G75 Nozzle - Red	25.00
HSZ463402	I31 / I25 / G75 Nozzle - White	25.00
HSZ463401	I31 / I25 / G75 Nozzle - Yellow	25.00
HSZ463404	I31 / I25 / G75 Nozzle -Light Brown	25.00
HSZ460010	I31 / I25 /G75 Nozzle Set	40.00
HSZ462459	I-40ADS Opposing Nozzle RK	25.00
HSZ462458	I-40ADS Std Nozzle RK (6 nozzles)	25.00
HSZ195803	I90 Blanking Nozzles - Left	2.00
HSZ195703	I90 Blanking Nozzles - Right	2.00

PRO SPRAY AND PG SERIES SPARES

Catalogue No	Description	Price £
HSZ462078	PGJ Check valve (bag of 25)	18.75
HSZ538700	PGJ nozzle rack	0.50
HSZ130900	PGP original Red Nozzle RK (12No)	0.50
HSZ466100	PGP Ultrashort Radius (6 x black)	0.50
HSZ233200	PGP.Orig. Low angle Nozzle RK (7No)	0.50
HSZ782900	PGP/I-20 Nozzle RK (8std,4 low)	0.50
HSZ213600	Pro-Spray Shut Off Cap - PK 5	10.00



Travelling sprinklers

POPE WATER TRACTOR



Travels along a 1/2" (12.5mm) hose at variable speed depending on flow and pressure.

It covers up to 15M diameter and is ideal for gardens.

Plastic construction with adjustable spray arms

Catalogue No	Description	Price £
69115-00	Water Tractor	98.00

RAIN TRAIN Travelling Sprinkler



- Custom watering along the path of the hose propelling itself along the ground following the pattern laid by the hose
- A shut off ramp is provided to automatically shut of the sprinkler
- Diameter of coverage 5 - 14meters, adjustable by twisting arms
- Minimum operating pressure 2.8bar (40psi)
- To be used with 1/2" or 3/4" hose

Catalogue No	Description	Price £
69-10-00	Rain Train Sprinkler	144.50
69-77360	Front Wheel Assembly	19.40
69-77361	Rear Wheel & Hub	19.40
69-77376	Plastic Motor Assembly c/w Shut Off	25.10
69-77506	Spray Arm Assembly	19.40
69-77529	Shut Off Ramp	9.70


NATIONAL B3 WALKING SPRINKLER



Body and wheels made of solid cast steel
Pulls 200-300' (60-90M) of hose up to 5/8"
Adjustable spray arms

Catalogue No	Description	Price £
69N20-00	Walking Sprinkler	382.00


PERROT ROLLCART-V



- Perrot's popular travelling sprinkler, Full and Part circle operation
- Connect hose to sprinkler, set arc & water upto 120 meters length
- Cord re-winds and pulls traveller along through a turbine driven pulley system
- Sprinkler radius upto 18 meters
- Speed of travel can be adjusted from 10 to 20 m/h
- Minimum operating pressure 3.5bar at the traveller
- Accurate distribution from Perrots ZE impact sprinkler
- Overall measurements 77 x 47 x 40 cm

Catalogue No	Description	Price £
69P10-00	RollcarT travelling sprinkler	1,460.00

REGA RAINKING



Professional Traveller.

Covers up to 38M width and with 135M cable will cover up to 175M length
Min. 4m³/hr at 3 bar pressure

Catalogue No	Description	Price £
69K25-00	Raining	1337.00
69KRL1030	Sprinkler Head	80.00

Working speed: 9.0 - 25 m/hr
Sprinkler Output: 4.3m³/h at 4 Bar
Diam of Coverage: 16-40M